

## Product info:

Dimensions: Width 2.00 m /2.50 m  
Length 30.00 m per roll (a minimum of 25.00m)

Tech. data:	Composition	25% polyester / 75% vinyl
	Yarn diameter	0.40 mm $\pm$ 5%
	Yarn thickness	0.84 mm $\pm$ 5%
	Warp/weft / cm	18 / 14
	Weight g/m <sup>2</sup>	580 g
	Fire class	M1
	Melting point	140°C
	Brittleness	- 25°C
	Air permeability	2200 l/m <sup>2</sup>
	Tensile strength	warp 175 daN $\pm$ 5% / weft 225 daN $\pm$ 5%
	Break elasticity	warp 5.6% / weft 19 daN $\pm$ 5%
	Initial tearing strength	> 1000 (ASTM D4966)
	Colour fastness	7 – 8
	UV resistance	Min. 4
	Expandability factor in %	$\pm$ 3
	Environmental certificate	ISO 14001:2004
	Sealband processing	183°C 4 sec. (Cooling time 5 sec)

Packaging: The fabric is wrapped around a sturdy cardboard sleeve and packed in transparent polyethylene. This is then shipped in a sturdy cardboard sleeve which is sealed using metal lids fitted with transportation handles.

Labels: Each roll is accompanied by a Quality Checklist, as well as a product information label with a unique EAN (bar)code.

Delivery: Delivery takes place direct from stock in accordance with our legally filed terms and conditions of delivery and payment.

Colours: The warp yarn forms the basic colour and the weft yarn the batch colour. Any colour is available, if a sufficient quantity is purchased. The basic range consists of the following colours:

- 0101 Grey / Grey
- 0102 Grey / White
- 0110 Sand / Grey
- 0130 Anthracite / Grey
- 0140 Blue / Grey
- 0702 White / Light grey
- 0707 Light grey / Light grey
- 1002 Sand / White
- 2002 Beige / White
- 3030 Anthracite/Anthracite